

- Flexible
- Easy to sand
- Stainable
- For softwood, hardwood, MDF & plasterboard

Please note that the colour illustrated is as near as the printing process permits

# Rustins

## Interior & Exterior

# Wood Filler

## White

**READY TO USE & FAST DRYING**

**Rustins Wood Filler is a fast drying, ready to use flexible filler that is easy to sand, stain and paint.**

**Suitable for interior and exterior use.**

#### Preparation:

The surface must be clean, dry and free of all traces of oil, grease and dust. Provide a key to smooth surfaces by lightly sanding with a medium grade of sandpaper.

#### Application:

Using a suitable filling knife, work the filler into the wood leaving it slightly proud for sanding. Deeper holes should be built up allowing 2 hours to dry between layers.

Once dry, the filler can be painted, stained or varnished

**Note:** Try a small inconspicuous area first as the filler may stain/varnish darker on the area filled.

#### Cleaning:

Clean tools in water immediately after use.

#### Storage:

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### Health and safety:

Contains 5-chloro-2-methyl-2h-isothiazol-3-one.

May produce an allergic reaction.

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Do not get in eyes, on skin, or on clothing.

IF ON SKIN: Gently wash with plenty of soap and water.


If skin irritation occurs: Get medical attention.

Wear protective gloves and eye protection.



EU Limit value for this product (CAT A1): 30g/l (2010)  
This product contains max 15g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)  
Telephone: +44 (0)20 8450 4666



**250ml e**

- Flexible
- Easy to sand
- Stainable
- For softwood, hardwood, MDF & plasterboard

Please note that the colour illustrated is as near as the printing process permits

# Rustins

## Interior & Exterior

# Wood Filler

## Mahogany

**READY TO USE & FAST DRYING**

***Rustins Wood Filler is a fast drying, ready to use flexible filler that is easy to sand, stain and paint.***

***Suitable for interior and exterior use.***

#### **Preparation:**

The surface must be clean, dry and free of all traces of oil, grease and dust. Provide a key to smooth surfaces by lightly sanding with a medium grade of sandpaper.

#### **Application:**

Using a suitable filling knife, work the filler into the wood leaving it slightly proud for sanding. Deeper holes should be built up allowing 2 hours to dry between layers.

Once dry, the filler can be painted, stained or varnished

**Note:** Try a small inconspicuous area first as the filler may stain/varnish darker on the area filled.

#### **Cleaning:**

Clean tools in water immediately after use.

#### **Storage:**

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### **Health and safety:**

Contains 5-chloro-2-methyl-2h-isothiazol-3-one. May produce an allergic reaction.

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Do not get in eyes, on skin, or on clothing.

IF ON SKIN: Gently wash with plenty of soap and water.


If skin irritation occurs: Get medical attention.

Wear protective gloves and eye protection.



EU Limit value for this product (CAT A1): 30g/l (2010)  
This product contains max 15g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)  
Telephone: +44 (0)20 8450 4666



5 015332 002320 >  
**250ml e**

- Flexible
- Easy to sand
- Stainable
- For softwood, hardwood, MDF & plasterboard

Please note that the colour illustrated is as near as the printing process permits

# Rustins

## Interior & Exterior

# Wood Filler

## Natural

**READY TO USE & FAST DRYING**

***Rustins Wood Filler is a fast drying, ready to use flexible filler that is easy to sand, stain and paint.***

***Suitable for interior and exterior use.***

#### Preparation:

The surface must be clean, dry and free of all traces of oil, grease and dust. Provide a key to smooth surfaces by lightly sanding with a medium grade of sandpaper.

#### Application:

Using a suitable filling knife, work the filler into the wood leaving it slightly proud for sanding. Deeper holes should be built up allowing 2 hours to dry between layers.

Once dry, the filler can be painted, stained or varnished

**Note:** Try a small inconspicuous area first as the filler may stain/varnish darker on the area filled.

#### Cleaning:

Clean tools in water immediately after use.

#### Storage:

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### Health and safety:

Contains 5-chloro-2-methyl-2h-isothiazol-3-one. May produce an allergic reaction.

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Do not get in eyes, on skin, or on clothing.

IF ON SKIN: Gently wash with plenty of soap and water.


If skin irritation occurs: Get medical attention.

Wear protective gloves and eye protection.



EU Limit value for this product (CAT A1): 30g/l (2010)  
This product contains max 15g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)  
Telephone: +44 (0)20 8450 4666



**250ml e**

- Flexible
- Easy to sand
- Stainable
- For softwood, hardwood, MDF & plasterboard

Please note that the colour illustrated is as near as the printing process permits

# Rustins

## Interior & Exterior

# Wood Filler

### Oak

**READY TO USE & FAST DRYING**

***Rustins Wood Filler is a fast drying, ready to use flexible filler that is easy to sand, stain and paint.***

***Suitable for interior and exterior use.***

#### Preparation:

The surface must be clean, dry and free of all traces of oil, grease and dust. Provide a key to smooth surfaces by lightly sanding with a medium grade of sandpaper.

#### Application:

Using a suitable filling knife, work the filler into the wood leaving it slightly proud for sanding. Deeper holes should be built up allowing 2 hours to dry between layers.

Once dry, the filler can be painted, stained or varnished

**Note:** Try a small inconspicuous area first as the filler may stain/varnish darker on the area filled.

#### Cleaning:

Clean tools in water immediately after use.

#### Storage:

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### Health and safety:

Contains 5-chloro-2-methyl-2h-isothiazol-3-one. May produce an allergic reaction.

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Do not get in eyes, on skin, or on clothing.

IF ON SKIN: Gently wash with plenty of soap and water.

If skin irritation occurs: Get medical attention.

Wear protective gloves and eye protection.



EU Limit value for this product (CAT A1): 30g/l (2010)  
This product contains max 15g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)  
Telephone: +44 (0)20 8450 4666



**250ml e**



- Flexible
- Easy to sand
- Stainable
- For softwood, hardwood, MDF & plasterboard

Please note that the colour illustrated is as near as the printing process permits

# Rustins

## Interior & Exterior

# Wood Filler

## Teak

**READY TO USE & FAST DRYING**

***Rustins Wood Filler is a fast drying, ready to use flexible filler that is easy to sand, stain and paint.***

***Suitable for interior and exterior use.***

#### Preparation:

The surface must be clean, dry and free of all traces of oil, grease and dust. Provide a key to smooth surfaces by lightly sanding with a medium grade of sandpaper.

#### Application:

Using a suitable filling knife, work the filler into the wood leaving it slightly proud for sanding. Deeper holes should be built up allowing 2 hours to dry between layers.

Once dry, the filler can be painted, stained or varnished

**Note:** Try a small inconspicuous area first as the filler may stain/varnish darker on the area filled.

#### Cleaning:

Clean tools in water immediately after use.

#### Storage:

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### Health and safety:

Contains 5-chloro-2-methyl-2h-isothiazol-3-one. May produce an allergic reaction.

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Do not get in eyes, on skin, or on clothing.

IF ON SKIN: Gently wash with plenty of soap and water.


If skin irritation occurs: Get medical attention.

Wear protective gloves and eye protection.



EU Limit value for this product (CAT A1): 30g/l (2010)  
This product contains max 15g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)  
Telephone: +44 (0)20 8450 4666



**250ml e**