

# Rustins

# Door Oil

## Clear Satin Natural Finish

### Hard wearing, water & stain resistant

Natural finish  
Easy to apply  
Easy to maintain  
Excellent coverage



**FOR SOLID WOOD & VENEERED DOORS**

Ideal for  
Solid wood doors  
Veneered doors  
Furniture  
Skirting boards  
Worktops  
Balustrades

### SHAKE WELL BEFORE USE

Rustins Door Oil is based on a mixture of natural vegetable oils, waxes and resins dissolved in white spirit giving an attractive, durable finish. Suitable for use on internal woodwork subject to a high degree of wear such as doors, floors and balustrades. The oil brings out the natural beauty of the wood and makes wood colours become richer/warmer. Rustins Door Oil is easy to apply and maintain, leaving a hard wearing, water and stain-resistant finish to woodwork.

### Preparation

The wood must be bare, or sanded clean of any previous coatings. The wood must also be smooth, dry and free from wax, dust and surface contaminants. Remove any waxes present with Rustins Surface Cleaner and a scouring pad. Wipe off residue with clean rags. Oily timbers such as Teak or Iroko must be wiped over with white spirit to remove surface oils which may inhibit drying and penetration of Rustins Door Oil. Nail holes may be filled with Rustins Wood Filler. Do not use knotting. Prior to using Rustins Door Oil it is advisable to test a small area first. Rustins Door Oil has been tested on a wide range of veneered doors but not all doors that are available on the market.

### Application

Use a brush, sponge or roller. Apply evenly in the direction of grain. Leave for a few minutes, then remove excess pools of material using a sponge or rag, spreading any excess oil evenly over the surrounding area. Note: Rustins Door Oil may darken some woods, therefore coating a test area first is advised. Rustins Wood Dye may be used under or mixed with Rustins Door Oil if desired. Test before proceeding if other brands of wood colourant are to be used.

### Maintenance

The wood cleaned with a wet cloth using a mild detergent solution. Dirt and scratches may

be removed by careful rubbing with a plastic scouring pad. If the surface has become dull or worn, it may be revived after cleaning, by re-oiling.

### Re-coating Time

4 - 6 hours, depending on temperature and humidity, optimum application temp. 15-25°C under dry, well ventilated conditions. Do not apply below 5°C.

### Coverage

1 litre will cover approximately 20-30 sq.m., depending on the nature and absorbency of the wood.

### Cleaning

Clean brushes with white spirit or Rustins Brush Cleaner if still wet. Hard brushes may be cleaned with Rustins Brush Restorer. Hardened oil may be removed using Rustins Strypit Paint & Varnish Stripper.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

### Storage

Many years in original sealed packaging if stored in cool, dry conditions.

### HEALTH AND SAFETY

Contains cobalt 6, zirconium drier 18%, methylethyl ketoxime. May produce an allergic reaction. Flammable liquid and vapour. Take precautionary measures against static discharge. Wear protective gloves.



WARNING

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. In case of fire: Use carbon dioxide for extinction. Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

UFI: NE75-G0JD-G008-X4PH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)


For information on Rustins products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Tel: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/I): 500g/l (2010).

This product contains max 487 g/l VOC.



**750ml e**