

August 2017

PRODUCT DATA SHEET

Product	Rust Converter
Type	A chemical treatment for the conversion of rust into a coating suitable for subsequent painting etc.
Intended Use	For use on corroded ferrous metal in order to facilitate refinishing.
Special Features	Ready to use. Water-based. Inhibits and neutralises rust. Stabilises the surface and forms a protective coating once dry. Rustins Rust Converter will form a barrier against water vapour, oxygen and carbon dioxide to prevent further rusting. Rustins Rust Converter will resist salt spray and bacterial growth.
Preparation	The surface must be clean, dry and free from oil and grease. Remove old paint and loose rust with steel wool or wire brush. If paint is difficult to remove use Rustins Strypit Paint and Varnish Stripper
Application	Stir/shake well before use. Pour the required amount needed into a plastic container. Do not return excess Rustins Rust Converter to this container. Brush a thin coat directly onto rusty areas only, working well into any pitted areas, corners and edges. Ensure that exposed corners and edges are well treated to avoid any chance of rust creep beneath.
Coats	One coat should be sufficient, but see re-coating times below.
Drying Time	30 minutes
Re-coating Time	Rustins Rust Converter will turn any treated areas blue-black as it reacts with rust. If the area treated does not change colour, reapply after 30 minutes. Do not rinse off the first treatment. Apply a topcoat after a minimum of 3 hours. For best results, paint the same day.
Application Temp.	Ideally between 15 – 25 degrees C.
Coverage	6-8 square metres per litre depending on the absorbancy of the surface.
Maintenance	N/A
Compatibility	Try on a small test area for compatibility before using.
Settlement	Stir/shake well before use.
Shelf-life/Storage	Many years in original unopened container stored in a cool, dry, dark place.
Hazards	WARNING. CAUSES SERIOUS EYE IRRITATION. Wash exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES; Rinse cautiously with water for several minute. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists seek medical advice/attention. For full safety data sheet visit www.rustins.co.uk
Clean-Up	Do not return excess Rustins Rust Converter to this container. Dispose of excess material according to local disposal regulations. Do not empty product into drains or water courses. Clean brushes immediately with water. If brushes become hard, clean with Rustins Brush Restorer or Rustins Cellulose Thinners .
Sizes	250 ml.