

AUGUST 2022

PRODUCT DATA SHEET

Product	15 Year Paint
Type	A moisture-cured single pack polyurethane paint available in white and yellow.
Intended Use	Primarily for marine use. Suitable for wood, aluminium, fibre-glass and smooth concrete.
Special Features	The coating is tough yet flexible and has excellent adhesion. A non-yellowing/chalking paint with high UV light protection for interior and exterior use. Typical Light Reflectance Value, (LRV) or Gloss/Sheen level approximately 90 %/gloss units at 60 degree viewing angle; where the final result depends on the condition of the surface onto which it is applied and how the paint coating is applied.
Preparation	Should be applied onto a bare, clean, dry substrate. Existing coatings, paint or other treatments should be removed first.
Application	Apply by brush, roller or spray.
Coats	Optimally apply 3 coats.
Drying Time	60 – 90 minutes depending on ambient conditions.
Re-coating Time	May be reapplied once surface is finger tacky. Do not attempt to recoat more than 4 hours after previous coat applied.
Application Temp.	Can be applied in poor weather conditions, high humidity and at temperatures down to freezing.
Coverage	500g/square metre.
Maintenance	Not applicable.
Compatibility	Suitable for wood, aluminium, fibre-glass and smooth concrete.
Settlement	Stir well before use.
Shelf-life/Storage	Many years if suitably stored in sealed original container. Note: product is moisture-cured, so shelflife will be limited for opened tins.
Hazards	FLAMMABLE. Irritant. Avoid contact with eyes and skin. Wear protective gloves and eye protection. In case of contact with eyes, immediately rinse eyes with plenty of water and seek medical attention. After contact with skin, wash immediately with soap and water or a suitable skin cleanser. Keep out of reach of children. Avoid ignition sources. Do not inhale vapour. Full safety data available on request or from www.bondaglass.com
Clean-Up	Clean equipment with Rustins Cellulose Thinners. Turpentine or White Spirit are unsuitable.
Sizes	1L.