

## **Expert finishes for wood and metal**

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

June 2020

## PRODUCT DATA SHEET

Product	All Star Wood Treatment.
Туре	Ultra-fine particle size wood preservative. BPR Authorisation Numbers: UK-2019-1194-4-31 and UK-2019-1194-5-31
Intended Use	Rustins All Star Wood Treatment is a water based, low odour, non-flammable product based on optimised formulation technology. The ultra-fine particle size allows deep penetration of the treatment to take place so the performance of the product is much greater than standard wood treatment products. It is non-flammable, quick drying and can be applied to wet or dry timbers. For preventative treatment against wood boring beetles, termites and wood rotting fungi. Also for curative treatment against wood boring beetles. For use on hard & soft wood. Requires sealing with a suitable film-forming paint or varnish, especially if used outside.
Special Features	Long-lasting all-purpose treatment, Prevents reinfestation of wood boring insects, wood rot and eliminates fungi. Easy to use. Low odour. Recoat while wet. For interior and exterior use.
Preparation	Ensure that timber surfaces are clean and free from previous coatings, grease and contaminants. Surfaces may be damp but the product should not be applied to decayed wood which will need to be removed and replaced.
Application	Shake well and stir before use. Apply two coats using a brush or low pressure spray. Exterior application must be by brush ONLY. Depending on the drying conditions, the second application should be applied before the first is dry. Ensure all end grain is thoroughly soaked as this is especially prone to water ingress and resulting decay.
Coats	Apply 2 coats.
Drying Time	Temperature and humidity will affect the rate of drying. It is important that after the first application the surface is not allowed to dry out and ideally should be damp when the second application is carried out.
Re-coating Time	Temperature and humidity will affect the rate of drying. It is important that after the first application the surface is not allowed to dry out and ideally should be damp when the second application is carried out. The timber should be allowed to dry for 48 hours before over-coating with a suitable film-forming paint or varnish as appropriate.
Application Temp.	Ideally 15 – 25 degrees Centigrade. Do not apply below 10 degrees Centigrade.
Coverage	Apply at a rate of 100 ml/ m2. (1L per 10 m2): For a preventative use against wood boring beetles. Apply at a rate of 152.8 - 200 ml/ m2. (1L per 5 m2): For a preventative use against wood rotting fungi. Apply at a rate of 200 ml/ m2. (1L per 5 m2): For a preventative use against wood boring beetles, termites and wood rotting fungi. Apply at a rate of 300 ml/ m2. (1L per 3.3 m2): For curative use against wood boring beetles
Maintenance	N/A

Compatibility	Not compatible with previous coatings, grease and contaminants.
Settlement	SHAKE WELL BEFORE USE.
Shelf-life/Storage	Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquid. Must only be kept in original packaging. Shelf life 2 years. Protect from frost.
Hazards	Spillage & Disposal: Collect spillage if safe to do so. Contain and collect spillage with a suitable absorbent and put into a securely sealed, leak proof container. Label container for disposal as hazardous waste. Avoid an accidental discharge into sewers, surface water or soil. Soil contaminated by the undiluted product should be treated as hazardous waste. In case of an accidental discharge of a large amount of the product to surface water, groundwater or sewer inform the appropriate authorities according to local regulations. Empty containers, unused product and other waste generated during treatment are considered hazardous waste. Dispose of in accordance with local regulations. Do not release to soil, ground, surface water or sewers.  Precautions:  Not to be used in and near food preparation area. Avoid contact with nonabsorbing surfaces like plastics, metal, bitumen and roofing felts. If in doubt, contact our technical department.  The colour illustrated on the tin is a guide only. Please try on inconspicuous area before proceeding with the whole job.  First Aid:  If medical advice is needed, have product container or label at hand. IF IN EYES: remove contact lenses, rinse with plenty of water for at least 15 minutes. IF ON SKIN: wash with soap and plenty of water, without rubbing. IF SWALLOWED: do NOT induce vomiting. If necessary attend hospital and show the label or packaging if possible. Do not leave poisoned person unattended. UK medical professionals should contact the National Poisons Information Service (www.npis.org) for further advice.  Pyrethroids and Pyrethrins may cause paraesthesia (burning and prickling of the skin without irritation). If symptoms persist get medical advice.  This product contains Permethrin; Pyrethroids can cause facial paraesthesia.  Poisoning may cause: Irritation or/and allergic skin reaction, irritation of eyes, mucosa, respiratory tract and gastrointestinal tract.  Do not use on wood which may come into direct contact or with food, feeding stuffs or livestock animals.
Clean-Up	Remove as much product as possible and return to this container. Brushes should then be cleaned immediately with water.
Sizes	5 litres.