

Rustins

QUICK DRY TEXTURED DECKING OIL BS7976 Rated LOW SLIP Potential

Rustins Quick Dry Textured Decking Oil
BS7976, Part 2, 2002 assessment of slip resistance.

Pendulum test value (PTV)

The pendulum slip test which forms the basis of BS7976 Pt. 2 - Determination of Slip resistance of flooring by the Pendulum Coefficient of Friction Test was developed from a collaboration by the Health and Safety Executive to ascertain the slip resistance of flooring.

The man-portable test apparatus uses a standard rubber slider to stimulate a shoe sole. The 'foot' swings from a horizontal release point, strikes the flooring surface under test travelling a known distance then reads off the test value on its over swing. This value will enable the determination of a coefficient of dynamic friction to be recorded for the test surface.

The table below shows the range of these coefficient factors and their contribution to the possibility of the test surface posing a slip risk:

	Pendulum test value (PTV)
High slip potential	0-24
Moderate slip potential	25-35
Low slip potential	36 and over

Rustins Textured Decking Oil PTV tested to more than 60 in dry conditions and more than 50 in wet conditions.

For more information on slip tests, please visit:
<http://www.hse.gov.uk/pubns/geis2.pdf>



- For hardwood & softwood
- Nourishes and protects
- Can be applied to damp timber
- Increased water repellency
- Hard wearing satin finish



The ultimate product for cleaning and reviving weathered garden decking. It is ideal for removing dirt, grease and stains prior to treatment with Rustins Quick Dry Decking Oil or Rustins Decking Stain & Seal. Ready for use - no need to dilute.



Perfect product for cleaning and reviving composite garden decking. It is ideal for removing dirt, grease and stains prior to treatment with Rustins Quick Dry Decking Oil. Ready for use - no need to dilute.

SHAKE WELL BEFORE USE

Rustins Quick Dry Textured Decking Oil is a water based, low odour, hard-wearing, water resistant oil that enhances the colour of the decking and contains agents to improve slip resistance on exterior timber and composite decking. Independently tested and rated as 'low slip potential' according to BS7976, Part 2, 2002 assessment of slip resistance. It contains UV light inhibitors that protect the oil from sunlight and can be applied whilst the decking is still damp. Use on composite, hardwood or softwood decking, it will leave a hard-wearing satin finish.

Preparation

The surface must be clean, dry and free from wax, algae, mould and other contaminants. Bare wood requires minimum 2 coats. If the deck is softwood or weathered extra coats may be required. The final colour will depend on the original colour of the wood and the number of coats applied. Where the deck is weather stained, discoloured, or of poor appearance use Rustins Decking Cleaner or Rustins Composite Decking Cleaner to clean and revive the surface.

Application

Stir well before use. Apply liberally using the largest brush practical. If applied thinly, this may affect the slip resistance properties. Synthetic bristle brushes designed for water-based varnishes are recommended. Try to keep a wet edge as overlapping a dry film will produce a darker patch, as will drips and runs. Do not apply when rain is expected. Do not use below 10°C, in damp conditions or if rain is imminent.

Re-Coating Time

Apply a minimum of three coats initially. The Textured Decking Oil will be dry in approximately 30 minutes depending on temperature and humidity. Further coats should be applied after a minimum of three hours. If applying over wood previously treated with a wood preserver test a small area first to ensure the decking oil dries and adheres well.

Maintenance

The finish will not flake or peel and will last many years if applied on a well prepared surface. From time to time, depending on exposure and use, decks will need re-oiling to maintain appearance and level of protection. When re-coating is necessary, clean the surface first with Rustins Decking Cleaner or Rustins Composite Decking Cleaner. Allow to dry then re-coat as above.

Coverage

1 litre will cover approximately 14 sq metres with 1 coat.

Cleaning

Remove as much product as possible and return to this container. Brushes should then be cleaned immediately with water. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY:

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Do not get into eyes, on skin, or on clothing.

Do not eat, drink or smoke when using this product.

Use personal protective equipment as required.



EU limit value for this product (cat A/h):
30g/l (2010).
This product contains max 22g/l VOC

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom or rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666



2.5 Litre e

For wooden and composite decking