



BRIWAX

QUICK DRY Hard Wax Oil

Hard wearing, water and stain resistant

Natural finish

Easy to apply

Easy to maintain

Excellent coverage



Made in UK



CLEAR SATIN FINISH

For interior use on:

Wood floors

Wood furniture

Wood skirting boards

Wood worktops

Wood balustrades

STIR WELL BEFORE USE

Briwax Quick Dry Hard Wax Oil is a water based, non-flammable oil which has a low odour when applying. Milky white whilst liquid, it will dry to a hard transparent satin finish. Suitable for use on internal woodwork subject to a high degree of wear; i.e. over wood flooring. The oil brings out the natural beauty of the wood and makes wood colours become richer/warmer. It is easy to apply and maintain, leaving a hard wearing, water and stain-resistant finish to woodwork.

Preparation

The wood must be bare or sanded clean of any previous coatings. The wood must also be smooth, dry and free from wax, dust and surface contaminants. Remove any waxes present with Rustins Surface Cleaner and a scouring pad. Wipe off residue with clean rags. Oily timbers such as Teak or Iroko must be wiped over with white spirit to remove surface oils which may inhibit drying and penetration of oil. Nail holes or narrow gaps may be filled with Rustins Floorboard Gap and Joint Filler. Do not use knotting.

Application

Use a brush, sponge or roller. Apply evenly in the direction of grain. Leave for a few minutes, then remove excess pools of material using a sponge or rag, spreading any excess oil evenly over the surrounding area. Note: Briwax Quick Dry Hard Wax Oil may darken some woods, therefore coating a test area first is advised for compatibility. Rustins Wood Dye may be used under the oil if desired. Test before proceeding if other brands of wood colourant are to be used.

Maintenance

The floor should be vacuumed or swept and then cleaned with a well-wrung cloth or mop, using a mild detergent solution. Dirt and scratches may be removed by careful rubbing with a plastic scouring pad. If the surface has become dull or worn, it may be revived after cleaning, by re-oiling.

Re-coating Time

The oil will be touch dry in approximately 30 minutes depending upon the temperature and humidity and can be re-coated after a minimum of two hours. Do not apply below 5°C.

Coverage

1 litre will cover approximately 20-30 sq.m., depending on the nature and absorbency of the wood.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Many years in original sealed packaging if stored in cool, dry conditions.

HEALTH AND SAFETY

Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Wear protective gloves/protective clothing/eye protection/face protection.

Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.



WARNING


For information on Briwax products visit our website at www.briwax.co.uk or contact us at Briwax International, Waterloo Road, London, NW2 7TX United Kingdom sales@briwax.co.uk

Telephone: +44 (0)20 8450 4666



EU Limit value for this product (CAT A/I): 130g/l (2010)

This product contains max 74 g/l VOC



1 Litre e