



PRODUCT DATA SHEET

Product	Wudfil Easy Stain Styrene-free Wood Repair Filler
Type	A styrene-free, two part wood filler, (filler + hardener) with an advanced formulation to make staining, painting and varnishing easier. Provides a strong long lasting repair for all interior and exterior wood work. Available in Mahogany, Pine, Teak, Oak, Cream and White colour.
Intended Use	For all types of interior and exterior timber.
Special Features	Styrene-free. The filler hardens within 10 -15 mins at ambient temperature. It can be sanded, drilled, machined and planed and is particularly useful for carrying out repairs to edges on joinery without crumbling where high strength is needed. Does not slump on application. Ideal for filling, cracks, holes, dents and splits. Specially formulated to facilitate uptake of wood stains after sanding.
Preparation	The surface must be clean, dry and free from all traces of oil, grease and dust. To provide good adhesion to timber, key smooth surfaces by lightly sanding with a medium grade of sand paper.
Application	Mix the filler with the hardener on a non-porous surface using an amount of filler the size of a golf ball to a pea-sized ball of hardener as the mixing ratio. Mix until an even colour is obtained. Do not prepare more than is required as any excess will be unusable within 5 - 7 mins. More hardener and/or high temperatures will decrease the hardening time. Using a putty knife or similar apply sufficient filler so that it is proud of the surface to allow a continuous smooth surface to be obtained by subsequent sanding.
Coats	Single application should be sufficient.
Drying Time	Approx. 10 – 15 minutes depending on temperature and humidity.
Re-coating Time	Once fully cured and after sanding back, most wood stains, varnishes and paints can be applied
Application Temp.	Ideally 15-25°C, but do not use below 10°C.
Coverage	N/A
Maintenance	N/A
Compatibility	Compatible under most finishes. For best results sand cure filler before staining and finishing.
Settlement	N/A
Shelf-life/Storage	12 months if stored in cool and dry place below 25 deg C in original, sealed packaging...
Hazards	Warning. Causes skin irritation. Causes serious eye irritation. Wear suitable protective gloves and eye/face protection. Wash hands, forearms and face thoroughly after handling. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. A full Health and Safety Data Sheet is available on request or on www.rustins.co.uk
Clean-Up	All tools must be cleaned immediately after use with Rustins Cellulose Thinners before product sets hard.
Sizes	