



Hotspot Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.ltd/hotspot

November 2022

## PRODUCT DATA SHEET

<b>Product</b>	<b>Stove Paint Matt Black</b>
<b>Type</b>	Ultra-high temperature, corrosion resistant, one coat finish.
<b>Intended Use</b>	Formulated for use on wood or multi-fuel stoves, gas coal/log effect fires, grates, baskets, fire backs, barbeques, pipes, flues etc.
<b>Special Features</b>	Extra coverage over conventional systems results from the high solids content.
<b>Preparation</b>	Ensure surface to be treated is cool and any heat source is extinguished, remove all rust, scale, dirt, grease and check the surface is dry. Only use thinners for paint tins.
<b>Application</b>	Stir well before use until there is no sediment on the bottom of the tin. Apply with a bristle paint brush. The paint may be sprayed but may require dilution with Xylene Thinners.
<b>Coats</b>	Only one light coat should be applied. If a heavy coat or more than one coat is applied, it is possible that the paint will flake from the surface.
<b>Drying Time</b>	The surface will be touch dry within 15 minutes and can be handled in 1 hour in good conditions. The painted article if air dried will become fully cured once it has been heated up to between 200 - 220°C for approximately 20 minutes. Once cured, heat resistant up to 600°C.
<b>Re-coating Time</b>	The paint should not be recoated.
<b>Application Temp.</b>	Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity.
<b>Coverage</b>	15 sq. metres/litre per coat depending on type of application and surface.
<b>Maintenance</b>	The previous coat will need to be removed if recoating becomes necessary. Wash with soapy water for general cleaning.
<b>Compatibility</b>	Bare ferrous metal.
<b>Settlement</b>	Stir or shake well before use.
<b>Shelf-life/Storage</b>	2 years if stored unopened in a cool, dry place.
<b>Hazards</b>	Flammable; harmful; harmful by inhalation and in contact with skin and eyes. Keep out of reach of children. Visit <a href="http://www.rustinltd/hotspot">www.rustinltd/hotspot</a> for full SDS. Caution: This product contains free silicone and precautions should be taken to isolate its processing from other paint systems.
<b>Clean-Up</b>	Clean up with xylene thinners.
<b>Sizes</b>	150ml, 250ml & 450ml aerosols & 100ml, 200ml & single 5 litre tins.