



Hotspot Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.ltd/hotspot

April 2024 (2)

PRODUCT DATA SHEET

Product	Fireplace Cleaner
Type	Liquid.
Intended Use	For removing smoke, soot and tar stains caused by wood, coal and gas fires, from brick, stone, concrete, marble and other hard surfaces.
Special Features	Brisk brushing creates foam, which cleans smoke stains, right down to the pores, without damage. Eliminates the need for harsh, damaging acids.
Preparation	Ensure surface to be cleaned is cool, remove screens, fixtures etc. and protect floors and carpets. Wear protective gloves and clothing. Wet the area to be cleaned with water.
Application	Pour Fireplace Cleaner onto a cloth and apply to the surface to be cleaned. Leave for approximately 1 minute and then rub vigorously with a damp cloth. Rough-textured or pock-marked surfaces will require brushing – an old nail or toothbrush is ideal.
Coats	As required.
Drying Time	Leave for 1 minute.
Re-coating Time	If stubborn stains remind, repeat treatment.
Application Temp.	15 – 25 degrees Centigrade.
Coverage	10 – 20 sq. metres per litre depending on the condition of the surface to be cleaned.
Maintenance	Use as required.
Compatibility	Do not use on cast iron and decorated or painted slate or stone. This product does not normally remove discolouration caused by weathering or natural impurities.
Settlement	Shake well before use.
Shelf-life/Storage	2 years if stored unopened in a cool, dry place.
Hazards	Corrosive; causes burns. Keep out of reach of children. For full product safety data visit www.rustinsltd/hotspot and download SDS.
Clean-Up	Rinse area thoroughly with water and remove surface water with absorbent cloth.
Sizes	500ml bottle.