

October 2020

PRODUCT DATA SHEET

Product	15 Year Paint
Type	A moisture-cured single pack polyurethane paint available in white.
Intended Use	Suitable for metal, wood, aluminium, fibre-glass and smooth concrete.
Special Features	The coating is tough yet flexible and has excellent adhesion. A non-yellowing, non-chalking high gloss paint with outstanding UV light protection.
Preparation	Should be applied onto a bare, clean, dry, rust-free substrate. May be applied to damp surfaces. Existing coatings, paint or other surface treatments should be removed first. Abrade surfaces where possible.
Application	Apply by brush, roller or spray. Note: carefully wipe excess material from lid and reseal otherwise rapid thickening will occur.
Coats	Optimally apply 3 thin coats as heavy coats may blister
Drying Time	60 – 90 minutes depending on ambient conditions.
Re-coating Time	May be reapplied once surface is finger tacky. Do not attempt to recoat more than 24 hours after previous coat applied.
Application Temp.	Can be applied in poor weather conditions, high humidity and at temperatures down to freezing.
Coverage	500g/square metre for 3 coats. Non porous surfaces: 140ml per sq. m per coat. Porous surfaces: 220ml per sq. m per coat. For wood and other slightly porous surfaces 3 coats are advised. For all porous surfaces 3 coats are necessary.
Maintenance	For repainting: rub down with abrasive paper and wash with a mild detergent solution, rinse thoroughly and allow to dry. Any small areas may be spot-primed with the paint, then apply 1 – 2 coats as required. The second coat should be applied within 24 hours for optimum results, but can be applied once previous coat is touch-dry. Note: carefully wipe excess material from lid and reseal otherwise rapid thickening will occur.
Compatibility	Suitable for metal, wood, aluminium, fibre-glass and smooth concrete.
Settlement	Stir well before use.
Shelf-life/Storage	Many years if suitably stored in sealed original container. Note: product is moisture-cured, so shelf-life will be limited for opened tins.
Hazards	FLAMMABLE. Irritant. Use in a well-ventilated area. Avoid contact with eyes and skin. Wear protective gloves plus hand cream and eye protection. In case of contact with eyes, immediately rinse eyes with plenty of water and seek medical attention. After contact with skin, wash immediately with soap and water or a suitable skin cleanser. Difficult to remove from skin. Keep out of reach of children. Avoid ignition sources. Do not inhale vapour. Full safety data available on request or from www.rustins.co.uk
Clean-Up	Remove as much product as possible from brushes before cleaning. Clean equipment with Rustins Cellulose Thinners. Turpentine or White Spirit are unsuitable
Sizes	1L