



Hotspot Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.ltd/hotspot

September 2020

PRODUCT DATA SHEET

Product	Stove Rope
Type	Glass fibre woven Stove Rope.
Intended Use	Suitable for most solid fuel stoves and boilers. It offers the best thermal resistance and is lightweight, yet still highly efficient as an insulator.
Special Features	It is suitable for temperatures up to 600°C and is resistant to oils, most chemical solvents and is unaffected by material growth.
Preparation	Clean away old stove rope and remove any loose/flaky metal from locating channel.
Application	Apply Hotspot Heatbond Rope Fixative following the instructions on the container. Press Stove Rope firmly into channel. Attach heat resistant tape to ends, then cut to size with scissors.
Coats	N/A
Drying Time	Allow 15 minutes before closing doors, the heat from the appliance will do the rest. If no heat source is available, please allow 24 hours to dry.
Re-coating Time	N/A
Application Temp.	N/A
Coverage	N/A
Maintenance	N/A
Compatibility	N/A
Settlement	N/A
Shelf-life/Storage	N/A
Hazards	N/A
Clean-Up	N/A
Sizes	1.5m pre-packed lengths of 6mm, 9mm or 12mm. 25m single reels are also available.