

Quick  
Dry

**Rustins**

# Door Oil

Hard wearing, water  
& stain resistant

Natural  
finish  
  
Easy to  
apply  
  
Easy to  
maintain  
  
Excellent  
coverage



**CLEAR SATIN NATURAL FINISH**

**FOR SOLID WOOD & VENEERED DOORS**

Ideal for  
  
Solid wood  
doors  
  
Veneered  
doors  
  
Furniture  
  
Skirting  
boards  
  
Worktops  
  
Balustrades

## SHAKE WELL BEFORE USE

Rustins Quick Dry Door Oil is a water based, non-flammable oil which has a low odour when applying. Milky white whilst liquid, it will dry to a hard transparent satin finish. Suitable for use on internal woodwork subject to a high degree of wear such as doors, floors and balustrades. The oil brings out the natural beauty of the wood and makes wood colours become richer/warmer. Rustins Quick Dry Door Oil is easy to apply and maintain, leaving a hard wearing, water and stain-resistant finish to woodwork.

## Preparation

The wood must be bare, or sanded clean of any previous coatings. The wood must also be smooth, dry and free from wax, dust and surface contaminants. Remove any waxes present with Rustins Surface Cleaner and a scouring pad. Wipe off residue with clean rags. Oily timbers such as Teak or Iroko must be wiped over with white spirit to remove surface oils which may inhibit drying and penetration of Rustins Door Oil. Nail holes may be filled with Rustins Wood Filler. Do not use knotting. Prior to using Rustins Quick Dry Door Oil it is advisable to test a small area first.

Rustins Quick Dry Door Oil has been tested on a wide range of veneered doors but not all doors that are available on the market.

## Application

Use a brush, sponge or roller. Apply evenly in the direction of grain. Leave for a few minutes, then remove excess pools of material using a sponge or rag, spreading any excess oil evenly over the surrounding area. Note: The oil may darken some woods, therefore coating a test area first is advised. Rustins Wood Dye may be used under Rustins Quick Dry Door Oil if desired. Test before proceeding if other brands of wood colourant are to be used.

## Maintenance

Clean wood with a wet cloth using a mild detergent solution. Dirt and scratches may be removed by

careful rubbing with a plastic scouring pad. If the surface has become dull or worn, it may be revived after cleaning, by re-oiling.

## Re-coating Time

The oil will be touch dry in approximately 30 minutes depending upon the temperature and humidity and can be re-coated after a minimum of two hours. Do not apply below 5°C.

## Coverage

1 litre will cover approximately 20-30 sq.m., depending on the nature and absorbency of the wood.

## Cleaning

Remove as much product as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

## Storage

Many years in original sealed packaging if stored in cool, dry conditions.

## HEALTH AND SAFETY

Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Wear protective gloves/protective clothing/eye protection/face protection. Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse.



WARNING

UFI: SAWE-50CW-N009-DG49


Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)

For information on Rustins products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Tel: +44 (0)20 8450 4666

ROF: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT Af):  
130g/l (2010)  
This product contains max 74 g/l VOC



750ml e