

February 2021

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Quick Dry Door Oil</b>
<b>Type</b>	<b>Rustins Quick Dry Door Oil</b> is a mixture of natural vegetable oils, waxes and resins emulsified in water giving an attractive, durable satin finish
<b>Intended Use</b>	For internal wooden doors and joinery.
<b>Special Features</b>	Brings out the natural beauty of the wood. Makes wood colours become richer. Easy to apply and maintain. Leaves a wear, water and stain resistant finish to woodwork
<b>Preparation</b>	The wood must be bare or sanded clean of any previous coatings. The wood must also be smooth, dry and free from wax, dust and surface contaminants. Remove any waxes present with <b>Rustins Surface Cleaner</b> and a scouring pad. Wipe off residues with clean rags. Oily timbers such as Teak or Iroko must be wiped over with white spirit to remove surface oils which may inhibit drying and penetration of <b>Rustins Quick Dry Door Oil</b> . Minor damage/splits may be repaired/filled with <b>Rustins Wood Filler</b> .
<b>Application</b>	Using a brush or roller, apply evenly in the direction of grain. <b>Rustins Wood Dye</b> may be used under <b>Rustins Quick Dry Door Oil</b> if desired. Test before proceeding if other brands of wood colourant are to be used.
<b>Coats</b>	Apply a minimum of 2 coats initially.
<b>Drying Time</b>	2 - 3 hours, depending on temperature and humidity. Touch dry in 30 minutes.
<b>Re-coating Time</b>	2 - 3 hours, depending on temperature and humidity. Touch dry in 30 minutes.
<b>Application Temp.</b>	Ideally 15-25 deg. C. Do not apply below 10 deg. C or in high humidity conditions.
<b>Coverage</b>	12 – 14 sq. m. per litre, depending on the nature of the wood.
<b>Maintenance</b>	The door should be cleaned with a well-wrung cloth or mop, using a mild detergent solution. Dirt and scratches may be removed by rubbing with a plastic scouring pad. If the surface has become dull or worn, it may be refinished after cleaning.
<b>Compatibility</b>	<b>Rustins Quick Dry Door Oil</b> may be used over the following Rustins products: <b>Rustins Wood Dye, Grain/Wood Filler</b> .
<b>Settlement</b>	Stir well before use.
<b>Shelf-life/Storage</b>	Many years in original sealed packaging if stored in cool, dry conditions.
<b>Hazards</b>	Avoid contact with eyes and skin. Use in a well-ventilated area. Keep out of reach of children. Keep container tightly closed. Full Product and Safety Data Sheets are available on request or from Rustins website <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	Clean brushes with water if still wet. Hard brushes may be cleaned with <b>Rustins Brush Restorer</b> . Hardened oil may be removed using <b>Rustins Strypit Paint &amp; Varnish remover</b>
<b>Sizes</b>	750ml