

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Stain Blocker aerosol</b>
<b>Type</b>	Solvent-based paint supplied in an aerosol-form containing a high pigment loading to provide excellent stain-blocking properties.
<b>Intended Use</b>	Rustins Stain Blocker has a matt white finish for interior and exterior use on wood, plaster and previously painted surfaces. It will seal all stains that may bleed through and discolour paint. As a primer, it provides excellent adhesion to ceramic tiles, glass, and melamine. When dry, it can be painted with any type of paint and undercoat. It can be applied over asphalt, bitumen, crayon, creosote, graffiti, nicotine, rust, soot, tannin and water stains.
<b>Special Features</b>	Low odour, quick-drying with excellent hiding power.
<b>Preparation</b>	Surfaces must be clean, dry and free from any grease or wax. Clean with water and detergent, rinsing with clean water. Remove any loose paint before applying Stain Blocker Aerosol.
<b>Application</b>	<b>SHAKE WELL BEFORE USE.</b> Use outdoors or in a well ventilated area. If using outside, avoid spraying if it is very windy or in dusty conditions. Shake can vigorously for approximately one minute from when the mixing balls start rattling. Continue shaking during use. Hold can upright approximately twelve inches from item spraying in a back and forth motion whilst spraying. Apply 2 or more light coats leaving a few minutes apart for each coat
<b>Coats</b>	One coat is recommended but a second coat can be applied if staining is severe.
<b>Drying Time</b>	Touch dry in 30 minutes, depending on temperature and humidity.
<b>Re-coating Time</b>	The surface will be dust dry after 30 minutes and can be handled after 1-2 hours. Allow longer during cooler temperatures. Re-coat after 1 hour.
<b>Application Temp.</b>	Ideally 15-25°C, do not use below 10°C or in conditions of high humidity.
<b>Coverage</b>	Approximately 10 sq. metres/litre per coat, depending on absorbency of surface.
<b>Maintenance</b>	N/A
<b>Compatibility</b>	All types of paint and undercoats.
<b>Settlement</b>	Shake well before use.
<b>Shelf-life/Storage</b>	Store in a cool dry place with the lid tightly closed. Do not expose to heat, sparks or open flame. The shelf life of the product is 2 years. The product can be used after the shelf life has expired but should first be checked to ensure it has not deteriorated in quality.
<b>Hazards</b>	DANGER. Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame and other ignition sources. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Repeated exposure may cause skin dryness or cracking. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains ACETONE, NAPHTHA (PETROLEUM), HYDROTREATED HEAVY. Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses. A full Safety Data Sheet is available upon request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a> UFI: PACF-N0VM-K002-6DJU
<b>Clean-Up</b>	When finished spraying, turn can upside down and spray to prevent clogging of the nozzle. Clean up paint with Rustins Xylene Thinners. If spray nozzle clogs, remove and clean using Rustins Xylene Thinners.
<b>Sizes</b>	400ml aerosol can

