

BW0502000047



BLACK

UFI: H39U-AE0J-F108-UTXP

WARNING



Flammable



Irritant

Contains Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C9, aromatics

H226 - Flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

UN No. 1263

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTRE if you feel unwell.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: H39U-AE0J-F108-UTXP



Briwax International. Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666

DIRECTIONS FOR USE



BRIWAX is a fast drying blend containing natural waxes suitable for use on most wooden surfaces.



SURFACE PREPARATION:

Unsealed wooden surfaces should be smooth, dry and clean. Apply BRIWAX using a lint free cloth or 0000 steel wool thoroughly working the wax into the grain. Once dry buff to desired finish with a clean soft cloth. Improved shine and durability can be achieved by first sealing the surface with BRIWAX Sanding Sealer. For antiques and pre-finished furniture, first check compatibility, then apply BRIWAX in small areas with a clean soft cloth.

The BRIWAX finish can be maintained by further applications which will give increased hardness and shine.



This product is not recommended for use in areas where it will come in contact with water. Above 20°C BRIWAX will soften and liquify. Replace lid, put in a cool place and it will return to its original state.

For information on Briwax products visit our website at www.briwax.co.uk or contact us at Briwax International, Waterloo Road, London, NW2 7TX United Kingdom sales@briwax.co.uk Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300

Content 370gms e



the natural wax

BRIWAX®

CLEANS, STAINS AND POLISHES

BLACK

WAX POLISH