

Nov 2023

PRODUCT DATA SHEET

Product	Quick Dry Varnish
Type	A low solids water-based acrylic protective coating.
Intended Use	For use on emulsion paint, wallpaper, plasterwork and other surfaces to protect against finger marks, stains, scuffing and colour fading.
Special Features	High UV resistance. Water, stain and abrasion resistant. Fast drying. Microporous. Suitable for interior and exterior use.
Preparation	Surface must be clean and free from dust, dirt, oil and contamination.
Application	Apply thin coats using a synthetic varnish brush. Dilute first coat with 10% water if to be used over porous surfaces.
Coats	2 – 3 coats. For a high durability.
Drying Time	One hour depending on ambient conditions.
Re-coating Time	One hour depending on ambient conditions.
Application Temp.	Ideally apply between 15 – 25 Centigrade. Avoid damp/high humidity conditions.
Coverage	15 – 20 square metres per litre.
Maintenance	Clean with soapy water.
Compatibility	Unsuitable for bare exterior woodwork or vinyl wall coverings. Unsuitable for continuous water immersion. Test over dark colours and porous emulsion paints.
Settlement	Stir well before use.
Shelf-life/Storage	Several years if stored unopened in a cool, dry place. Protect from frost.
Hazards	
Clean-Up	Wash application equipment with warm soapy water.
Sizes	500ml Flat Matt and Satin finishes