

www.woodfillers.co.uk

BRUMMER • STOPPING •

WOODFILLER FOR INTERIOR & EXTERIOR



Preparation: The surface must be clean dry and free of all traces of oil, grease and dust. Provide a key to smooth surfaces by lightly sanding with a medium grade of sandpaper. Application: Using a suitable filling kinfe, work the filler into the wood leaving it slightly proud for sanding. Deceper holes should be built up

Deeper holes should be built up allowing 2 hours to dry between layers. Once dry, the filler can be painted, stained or varnished.

Note: Try a small inconspicuous area first as the filler may stain / varnish darker on the area filled.

Cleaning: Clean tools in water immediately after use.

Storage: Store in a cool dry place with the lid tightly closed. Protect from frost. Health and safety: Contains Schloro Zmethyl Zhisothizavi 3-one. May produce an allergic reaction. Keep out of reach of children. IF SWALLOWED: Call a POISON CENTRE/doctor fry usel eu nunell. Do not get in eyes, on skin, or on clothing. IF ON SIGN. Gently wash with plenty of saga and water.

DIRECTIONS

Wear protective gloves and eye protection.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. UFI: CXH7-30H2-M00G-YH38